

Tac-FAST

CARPET TILE ADHESIVE

Features

- ✓ Speed of application
- ✓ Self contained low maintenance system
- ✓ Low odour
- ✓ Fast drying time
- ✓ Even coverage
- ✓ Moisture resistant
- ✓ Long lasting high tack adhesion

Surface Preparation

All surfaces must be clean, dry and free from oil, grease and paint. Any excessive dust must be removed as failure to do so will impair the performance of the adhesion. If applying the adhesive directly on to concrete, or sand and cement screeds, they must be fully cured and laitance free. If applying to earth subfloors an efficient damp proof membrane must be incorporated.

Site conditions must comply with British Standards CP 102 (Code of practice for protection of building against water from underground), BS 5325 (Installation of textile floor coverings) and all supplementary publications must be followed throughout the installation.

TAC-FAST is a fast drying, high tack carpet tile adhesive. It is designed for bonding carpet tiles to a wide range of substrates including wood, metal and concrete. The bulk aerosol system has no wastage and has proved to be seven times fast than the traditional trowelling of adhesives.

To apply the adhesive simply position the wand approximately 40-50cm from the floor and spray the adhesive evenly in a thin layer moving constantly across the area to be coated. In order to achieve a releasable bond allow the adhesive to dry, it will adopt a clear appearance as it does so, depending on the thickness of coverage and the room atmosphere this will take approximately 10 minutes. Once the carpet tiles have been laid they can be repeatedly lifted without damaging the adhesive or substrates, however if the tiles are laid whilst the adhesive is still wet a permanent bond will be formed.

If the system is to stand unused for a while then it is advisable to flush it out with Gemini Adhesives GUNWASH so it is ready for instant use in the future.

It is the users responsibility to ensure that the adhesive is suitable for the substrates to be bonded, if you are unsure please contact our technical department for assistance.

Technical Data

- Coverage approximately 500 sq meters
Higher coverage achieved on perfect or metal access floors
- Appearance clear liquid
- Zero VOCS
- Non flammable
- Solvent free
- Water based



Gemini II
II Adhesives

Gemini Adhesives Limited

New Building, Top Road, Osgathorpe, Loughborough, Leics, LE12 9TB. Telephone: 01530 224712 Fax: 01530 223514

www.geminiadhesives.com